

Type by Model	PRODUCT CATEGORY OF MIURA BOILER BY TYPE							
	GAS [LPG/NG]	OIL	ELECTRIC	DUAL FUEL		HOT WATER		HOT OIL
				OIL	GAS [LPG/LNG]	OIL	GAS [LPG/LNG]	OIL/LNG
AI Series		AI-500 AI-750 AI-1000 AI-1500 AI-2500 AI-3000 AI-4000						
EI Series	EI-1000GH/GS EI-1500GH/GS EI-2000GU	EI-1000H/S EI-1500H/S EI-2000S			EI-1500HGO EI-1500SGO EI-2000SGO			EI-1500C
		EI-1000HGO/SGO EI2000 SGO						
EX Series		EX-500 EX-750						
EW & EW-N Series						EW-30H/W EW-40H/W EW-50H/W EW-60H/W EW-80H/W EW-30NS/NW* EW-40NS/NW* EW-50NS/NW* EW-60NS/NW* EW-80NS/NW*	EW-30GNS/GNW* EW-40GNS/GNW* EW-50GNS/GNW* EW-60GNS/GNW* EW-80GNS/GNW*	
EH Series		EH-500F EH-750F EH-1000F EH-1500X						
GC Series					GC-2000ZH/ZS			
GX Series	GX-120S GX-160S GX-250S GX-350S							
ME Series			ME-10 ME-20 ME-30 ME-40 ME-50					
SI Series		SI-1500VH/VS SI-2000VH/VS SI-2000**						
SQ Series	SQ-800ZS SQ-1000ZS SQ-1200ZS SQ-2000ZS SQ-2500ZS							
SU Series	SU-250H/S SU-350H/S	SU-160 SU-200 SU-300 SU-400						
SZ Series		SZ-100L						

Remark.

AI: Multi-Control system for stable steam supply

EI: Small Once Through Steam Boiler with Multi-Control System for Stable Steam Supply. [max efficiency of 96% w/ Gas], [max efficiency of 95% w/ Oil]

EX: Simple Once Thorough Steam Boiler with Safe Design Prevents Boiler Overheating. [max efficiency of 95% w/ Gas LowNox]

EW: Small Once Through Hot Water Boiler with Heat-efficient water tube construction for outstanding energy saving.

* EW-N: Hot Water Heater with Sample Operation.

EH: Simple Once Through Steam Boiler with Low Priced, Long selling product and reliable functions.

GC: Small Once Through Steam Boiler with Low excess air combustion. [max efficiency of 95%]

GX: Simple Once Through Steam Boiler with ECO-friendly low Nox Specification (Except models 40, 60 and 90) [max efficiency of 88% w/ Gas LowNox]

ME: Simple Once Through Steam Boiler with No emissions

SI: Small Once Through steam Boiler with ECO-Friendly low Nox boiler. [max efficiency of 95% w/ Oil]

SQ: Small Once Through Steam boiler with Ultra low Nox and CO emissions. [max efficiency of 96% w/ Gas LowNox]

SU: Simple Once Through Steam Boiler with ECO friendly with low Nox (13A) and low air ratio. [max efficiency of 90% w/ Oil and Gas LowNox]

SZ: Simple Once Through Steam Boiler with Lower Capacity boiler that exploits all of the advantages of steam. [max efficiency of 90% w/ Oil LowNox]

** SI2000: This model can used with Oil and Gas.